


EE



COMPLEX PRO 14 LITE



COMPLEX PRO 14 LITE Specification

Processor / Core Logic	<ul style="list-style-type: none"> • Intel® Core™ i7-1260P processor (2.1GHz, up to 4.7GHz) • Intel® Core™ i5-1240P processor (1.7GHz, up to 4.4GHz) • Intel® Core™ i3-1220P processor (1.5GHz, up to 4.4GHz)
Display	• 14.0" (35.56cm) FHD (1920x1080) 16:9 panel, 2.4mm
Memory	<ul style="list-style-type: none"> • Dual channel DDR4 • Two 260 pins SODIMM sockets, support DDR4 up to 3200 MHz (Real operation frequency depends on processor) • Expandable memory up to 64GB, depends on 8GB/16GB/32GB SODIMM module
Video Controller	<ul style="list-style-type: none"> • Intel® Iris® Xe Graphics (i7-1260P / i5-1240P) <ul style="list-style-type: none"> - Intel® Xe Micro architecture - 8K HDR Support - Variable Rate Shading • Intel® UHD Graphics (i3-1220P) <ul style="list-style-type: none"> - HDR Support - Rec. 2020 (Wide Color Gamut) - Microsoft DirectX® 12 compatible
Storage	• One M.2 2280 SSD, PCIe Gen4x4 interface
Audio	<ul style="list-style-type: none"> • High Definition Audio • Built in array microphone • Built in two speakers
Keyboard and Pointing Device	<ul style="list-style-type: none"> • Multi languages A4 size isolated keyboard • (Option) Multi languages A4 size isolated illuminated keyboard (White Color) • Built in Click Pad with Microsoft PTP multi-gesture and scrolling function
I/O ports	<ul style="list-style-type: none"> • 1 x Thunderbolt™ 4 combo port with Power Delivery DC in (Type C) • 1 x USB 3.2 Gen 2 ports (Type C) • 2 x USB 3.2 Gen 1 port (Type A) • 1 x HDMI™ output port (with HDCP) • 1 x 2-in-1 Audio Combo Jack (Headphone / Microphone) • 1 x RJ-45 LAN port • 1 x DC-in jack 
Card Reader	<ul style="list-style-type: none"> • 6-in-1 Card reader <ul style="list-style-type: none"> - MMC / RSMCMC - SD / mini SD / SDHC / SDXC
Slot	<ul style="list-style-type: none"> • Two M.2 card slots <ul style="list-style-type: none"> - 1st for WLAN Combo M.2 2230 Card with PCIe/USB/CNVi interface (E Key) - 2nd for SSD M.2 2280 Card with PCIe Gen4x4 interface (M Key)
Communication	<ul style="list-style-type: none"> • Built in 10/100/1000Mb Base-TX Ethernet LAN • (Factory Option) Intel® Dual Band Wi-Fi 6E AX211 2x2 AX + BT CNVi M.2 2230 (Garfield Peak 2) • (Factory Option) Intel® Dual Band Wi-Fi 6E AX210 2x2 AX + BT PCIe M.2 2230 (Typhoon Peak 2) • (Factory Option) Intel® Dual Band Wi-Fi 6 AX201 2x2 AX + BT CNVi M.2 2230 (Harrison Peak 2) • (Factory Option) Intel® Dual Band Wireless-AC 9462, 1x1 AC + BT M.2 2230 (Jefferson Peak 1) • 1.0M HD video camera • (Factory Option) Windows Hello Camera
Power Supply	<ul style="list-style-type: none"> • Full Range AC adapter, AC in 100~240V, 50~60Hz, DC output 19V, 4.74A, 90W • Embedded 4 cells Smart Lithium-Ion battery pack, 53.35WH • Battery life : 680 minutes (UMA mode with 53.35WH battery)
Security	<ul style="list-style-type: none"> • Security (Kensington® Type) Lock Slot • Intel® PTT for system without Hardware TPM • (Factory Option) TPM 2.0
Others Design	<ul style="list-style-type: none"> • Metal (A) • Shipping Mode • FlexiCharger • Windows® Mixed Reality Compatible • Intel® DTT
OS Support	• Windows®11 (64-bit)
Certificate	<ul style="list-style-type: none"> • Windows®11 (64-bit) Logo • HDMI™ Logo
Dimension	• 324.9 (W) x 225 (D) x 17.6 (H) mm
Weight	• 1.35 kg, Including Barebone and 53.35WH Battery

2022/07 Version

Remark:
 *Battery life may vary depending on applications and configuration.
 *Weight tolerance is +/- 5%.
 *The content is subject to change without notices. Other brand and product names are trademarks and/or register trademarks of their respective companies.